


EN210/91RN-156D- 735/740/745/750/755/760W

Bifacial Dual Glass TOPCON Monocrystalline Solar Module 156 Half-cell Series

ABOUT ECONESS ENERGY

Established in 2009, Econess Energy is engaged in PV power station development and PV module production. With current annual production capacity of 12GW modules, Econess Energy now distributes its PV products all over the world, such as Germany, Spain, Italy, France, India, Japan etc. As a strong, bankable partner, we are committed to building strategic, mutually beneficial collaboration with installers and developers.



KEY FEATURES

-  **Multi Busbar Technology**
Better light trapping and current collection to improve module power output and reliability
-  **Bifacial power generation**
Bifacial cell technology, 5% to 25% more yield depends on different conditions
-  **Lower temperature coefficients**
Enhance power generation
-  **Enhanced Mechanical Load**
Certified to withstand: wind load (2400 Pa) and snow load (5400 Pa)
-  **IP68 junction box**
High waterproof level
-  **High customer value**
Lower BOS cost and LCOE


SYSTEM CERTIFICATES

- ISO 9001 : 2015 Quality Management System
- ISO 14001 : 2015 Environment Management System
- ISO 45001 : 2018 Occupational Health and Safety Management System

QUALITY WARRANTY

Econess Energy guarantees that defects will not appear in materials and workmanship defined by IEC61215 or IEC61730 under normal installation, use and maintenance as specified in Econess Energy's installation manual for 15 years from the warranty starting date.

PERFORMANCE WARRANTY



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 - +5w)

Maximum Power(Pmax/W)	735	740	745	750	755	760
Operating Voltage (Vmpp/V)	48.71	48.81	48.91	49.01	49.11	49.21
Operating Current(Imp/A)	15.10	15.17	15.24	15.31	15.38	15.45
Open-Circuit Voltage (Voc/V)	58.21	58.40	58.59	58.78	58.97	59.16
Short-Circuit Current(Isc/A)	16.00	16.05	16.10	16.15	16.20	16.25
Module Efficiency η_m (%)	22.88	23.04	23.20	23.35	23.51	23.66

Performance at BNPI

Maximum Power(Pmax/W)	814	820	825	831	837	842
Operating Voltage (Vmpp/V)	48.86	48.96	49.06	49.16	49.26	49.36
Operating Current(Imp/A)	16.67	16.75	16.83	16.90	16.98	17.06
Open-Circuit Voltage (Voc/V)	58.36	58.55	58.74	58.93	59.12	59.31
Short-Circuit Current(Isc/A)	17.73	17.78	17.84	17.89	17.95	18.01


STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5

BNPI: Efront =1000W/m², Erear =135W/m²

MECHANICAL SPECIFICATION

Cell Arrangement	156 [2 x (13 x 6)], 210 x 182 mm
Weight	38.9 kg(85.76 lb)
Module Dimensions	2465 x1303 x 33mm(97.05 x 51.30x1.30 inch)
Cable	350mm (13.78 inch) · 4 mm ² (0.006 sq.in)
Front Glass	2.0 mm High Transmission, Tempered Glass
Packing Configuration	33pcs/Pallet, 264pcs/40hq
Frame	Anodized aluminum alloy or customizable composite frame
Junction Box	IP68


I-V CURVE



OPERATING CONDITIONS

Maximum System Voltage	1500V (IEC/UL) DC
Operating Temp	-40°C ~ +85°C
Maximum Fuse Rating	35 A
Static Loading	5400 Pa
Connector	MC4 Compatible

TECHNICAL DRAWINGS (mm)



TEMPERATURE COEFFICIENT

Temperature Coefficient(Pmax)	-0.29%/°C
Temperature Coefficient(Voc)	-0.25%/°C
Temperature Coefficient(Isc)	+0.043%/°C
NOCT	41±2°C